

# High Density 1U Fiber Connect Panel System

## HIGH-DENSITY FCP3 FIBER CONNECT PANEL

Economically connect, protect and manage up to 96 LC fiber ports within 1 rack mount space. Designed to integrate with high-density FCP3 fiber plug and play modules (details below).



### High Density

Supports up to 96 fibers in just 1 rack-mount space

### Enhanced Accessibility

Fiber drawer slides to the front and rear for maximum access to fiber connections

### Bend Radius Management

Recessed modules provide a high-capacity jumper management zone that helps maintain proper fiber bend radius



## HIGH-DENSITY FCP3 PLUG AND PLAY MODULES AND ADAPTER PLATES

Siemon LC to MTP® FCP3 Plug and Play modules are designed for simple, snap-in deployment within the high density FCP3 fiber connect panel. Providing 24 LC ports per module, these factory terminated and tested modules are available in OM3 and OM4 multimode and singlemode configurations.



### High Density

Modules provide 24 LC ports per module, supporting up to 96 ports within the 1U FCP3 fiber connect panel

### Fast Deployment

Snap-in mounting and multi-fiber MTP connectivity offers ultra-fast deployment of high-performance fiber channels

### Compact Housing


Reduces mounting depth for greater cable management space within enclosures

### Optimized Adapter Spacing

Enables easy finger access to fiber jumper connector latches in high density patching environments


### Multimode and Singlemode Modules

Utilize zirconia ceramic sleeves for optimum performance




# PRODUCT INFORMATION

## Ordering Information: Enclosure Accessories



- FCP3-DWR-4..... High-density FCP3 Fiber Enclosure, black
- PPM-BLNK ..... High-density FCP3 Blank Panel Filler, black

## Ordering Information: Modules and Adapter Plates



- PPM-(XX)-LC(XX)-01 ..... 24 Port LC P&P Module with 2 MTP ports, black
- | Fiber Count              | Fiber Type                     |
|--------------------------|--------------------------------|
| 12 = 12 (1MTP Adapter)   | 5L = XGLO 300 50/125 Multimode |
| 24 = 24 (2 MTP Adapters) | 5V = XGLO 550 50/125 Multimode |
|                          | SM = Singlemode                |
- 
- PPM-F-LC(X)(XX)-01 ..... High-density FCP3 LC Adapter plates
- | Fiber Type       | Fiber Count   |
|------------------|---------------|
| BLANK = Biege MM | 12 = 12 Fiber |
| U = Blue SM      | 24 = 24 Fiber |

## PERFORMANCE

Fiber Type		MAX Insertion (db)		MAX Return Loss (db)		Performance Class
		MTP	LC	MTP	LC	
5L-MM	50/125 10G (OM3)	0.50	0.25	20	30	XGLO™ 300
5V-MM	50/125 10G (OM4)	0.50	0.25	20	30	XGLO™ 550
SM-LWP	SM (OS2)	0.75	0.40	55	55	XGLO™

**For additional resource information:**

Visit our web site at [www.siemon.com](http://www.siemon.com)

**North America**

Watertown, CT USA  
 Phone (1) 860 945 4200 US  
 Phone (1) 888 425 6165 Canada

**Europe/Middle East/Africa**

Surrey, England  
 Phone (44) 0 1932 571771

**Asia/Pacific**

Shanghai, P.R. China  
 Phone (86) 21 5385 0303

**Latin America**

Bogota, Colombia  
 Phone (571) 657 1950